



Datasheet



# Colour Manager

- High volume output performance – in B&W and Full Colour.
- Seamless integration into your office, network and enterprise.
- Enhanced operability takes ease of use to a new level.
- Solid security for easy and intelligent control of your documents and information.

**e-STUDIO5520c**

**e-STUDIO6520c**

**e-STUDIO6530c**



Networking Documents.

**TOSHIBA**  
Leading Innovation >>>



**e-STUDIO5520c**  
**e-STUDIO6520c**  
**e-STUDIO6530c**



<p><b>General</b></p>	<p><b>Print &amp; Copy Speed</b>  <b>Warm-up Time</b>  <b>Paper Size &amp; Weight</b>  <b>Paper Capacity</b>  <b>Automatic Duplex Controller Type</b>  <b>Memory Interface</b>  <b>Dimensions &amp; Weight</b></p> <p>Colour: 55/65/65 ppm (A4), 27/30/30 ppm (A3)          B&amp;W: 55/65/75 ppm (A4), 27/30/37 ppm (A3)          Approx. &lt;70 seconds from low-power mode          Cassettes: A5R-320 x 460 mm, 64-256 gsm          Tandem LCF<sup>2)</sup>: A4, 64-256 gsm          Bypass: A6R-13" x 19", 64-300 gsm, banner paper 313 x 1,200 mm, 64-256 gsm          4 x 540 sheets (Cassettes) or 2 x 540 sheets (Cassettes) + 2,320 sheets (Tandem LCF)<sup>2)</sup>, 100 sheets (Bypass)          Maximum: 6,000<sup>2)</sup> sheets with external LCF<sup>1)</sup>          Up to 320 x 460 mm and 256 gsm          Toshiba e-BRIDGE          80 GB HDD, 2.0 GB RAM          10/100/1000BaseT (incl. IPv6), High-Speed USB 2.0, WLAN<sup>1)</sup> (IEEE802.11b/g), Bluetooth<sup>1)</sup>          980 x 698 x 1,540 mm (W x D x H), ~ 246 kg</p>
<p><b>Print</b></p>	<p><b>Resolution</b>  <b>Page Description Language Supported Systems</b>  <b>Colour Modes</b>  <b>Colour Settings</b></p> <p>Max. 600 x 600 dpi, 8 bit per channel          Max. 1,200 x 1,200 dpi, 2 bit per channel<sup>3)</sup>          XPS, PCL6 and PostScript 3 compatible          Windows 2000, Windows XP/Server2003/Server 2008/Vista (32/64 bit), Mac OS X, Linux/UNIX, Novel Netware (NDPS), Citrix, SAP, AS/400          Auto-Colour (ACS), Colour, Grayscale, B&amp;W          Brightness, Saturation, Contrast, Colour Balance</p>
<p><b>Scan</b></p>	<p><b>Resolution</b>  <b>Scan Speed</b>  <b>Document Feeder</b>  <b>Scan Modes</b>  <b>File Formats</b>  <b>Scan Functions</b></p> <p>Max. 600 x 600 dpi, 8 bit per channel          Colour &amp; B&amp;W: Up to 77 pages/min. (300 dpi)          Max. 100 sheets, A5R-A3, 35-209 gsm          Auto-Colour (ACS), Colour, Greyscale, B&amp;W          JPEG, Multi/Single Page TIFF, Multi/Single Page XPS, Multi/Single Page PDF, Secure PDF, Slim PDF (high compression), Searchable PDF<sup>1)</sup> (and other editable formats like DOC, XLS, RTF, TXT)<sup>1)</sup>          WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP), Meta Scan<sup>1)</sup>, Scan to Box (e-Filing), TWAIN 1.7</p>
<p><b>Copy</b></p>	<p><b>Resolution</b>  <b>First Copy</b>  <b>Zoom</b>  <b>Copy Modes</b>  <b>Colour Modes</b>  <b>Colour Settings</b></p> <p>Scanning: 600 x 600 dpi, 10 bit per channel          Printing: 600 x 600 dpi, 8 bit per channel          2,400 x 600 dpi, B&amp;W with smoothing          Colour: Approx. 6.5 seconds          B&amp;W: Approx. 5.3/5.3/4.6 seconds          25-400% (platen glass), 25-200% (RADF)          Text, Text/Photo, Photo, Printed Image, Map          Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&amp;W          Hue, Saturation, Colour Balance, 5 One-touch Modes, RGB Adjustment</p>
<p><b>Fax<sup>1)</sup></b></p>	<p><b>Communication</b>  <b>Transmission Speed</b>  <b>Compression</b>  <b>Network-Fax</b>  <b>Incoming Fax Routing</b></p> <p>Super G3, G3 - (opt. 2<sup>nd</sup> line), Internet Fax T.37          Approx. 3 seconds per page          JBIG, MMR, MR, MH          Driver for Windows 2000/XP/Vista (32/64 bit)          To shared folder (SMB, FTP), e-mail, e-Filing</p>
<p><b>System &amp; Security</b></p>	<p><b>Device Management</b>  <b>System Features</b>  <b>Accounting &amp; Security</b></p> <p>e-BRIDGE Fleet Management Software<sup>1)</sup>, TopAccess remote administration &amp; configuration          e-Filing document server for secure storage, document distribution and Print-on-Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan preview, Print from USB, e-BRIDGE Open Platform<sup>1)</sup>          Role Based Access, LDAP support, 1,000 department codes &amp; 10,000 user codes, card reader support, private print, standard data encryption, Data Overwrite Kit<sup>1)</sup>, IP and MAC address filter, port filter, support of SSL and IPsec<sup>1)</sup> protocol, IEEE802.1x support, Scan to secure PDF</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 gsm if not otherwise mentioned.</p>

**OPTIONS**

**MULTI-STAPLE FINISHER – MJ-1103**  
 2 trays, 3,250 sheet capacity  
 50 sheet multi-position stapling  
 A5R-A3, 64-105 gsm (staple mode)  
 617 x 603 x 1,085 mm (W x D x H), ~ 40 kg

**SADDLE-STITCH FINISHER – MJ-1104**  
 2 trays, 3,250 sheet capacity  
 50 sheet multi-position stapling  
 Saddle-stitched booklets of up to 60 pages  
 A5R-A3, 64-105 gsm (staple mode)  
 617 x 603 x 1,085 mm (W x D x H), ~ 70 kg

**HOLE PUNCH UNIT – MJ-6102**  
 Option for Finisher MJ-1103/MJ-1104  
 Available in 2-holes (E), 4-holes (F),  
 112 x 573 x 323 mm (W x D x H), ~ 7 kg

**LARGE CAPACITY FEEDER – MP-2501A**  
 2,500 sheet capacity, A4, 64-256 gsm  
 360 x 552 x 542 mm (W x D x H), ~ 29 kg

**OTHER OPTIONS**  
 FAX BOARD GD-1270EU  
 DATA OVERWRITE KIT GP-1070  
 E-BRIDGE ID-GATE KP-2004/KP-2005  
 IMAGING ACCELERATION BOARD GE-1170  
 WIRELESS LAN ADAPTER GN-1050  
 BLUETOOTH ADAPTER GN-2010  
 META SCAN ENABLER GS-1010  
 WEB-SERVICES ENABLER GS-1020

<sup>1)</sup> Optional  
<sup>2)</sup> e-STUDIO5520c tandem LCF version only  
<sup>3)</sup> PostScript driver only

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. D56530c00B0808

**TOSHIBA TEC UK  
 IMAGING SYSTEMS LTD**

ABBAY CLOISTERS, ABBAY GREEN,  
 CHERTSEY, SURREY, KT16 8RB.  
 TEL 01932 580100 FAX 01932 580101  
 WWW.TOSHIBA.CO.UK/IMAGING