



Datasheet



# Colour Manager

- Copy - Scan - Print - Fax - Connect - Store
- Excellent colours enhancing your document quality
- Highly intuitive user interface
- Hassle free integration into your network

- e-STUDIO2040c**
- e-STUDIO2540c**
- e-STUDIO3040c**
- e-STUDIO3540c**
- e-STUDIO4540c**



SAP® Printer Vendor Solution



Networking Documents.

**TOSHIBA**  
Leading Innovation >>>



**e-STUDIO2040c**

**e-STUDIO2540c e-STUDIO3540c**

**e-STUDIO3040c e-STUDIO4540c**



<p><b>General</b></p>	<p><b>Print &amp; Copy Speed</b> Colour: 20/25/30/35/45 ppm (A4), 10/15/16/18/22 ppm (A3) B&amp;W: 20/25/30/35/45 ppm (A4), 10/15/16/18/22 ppm (A3)</p> <p><b>Warm-up Time</b> Approx. 30 seconds from low-power mode</p> <p><b>Paper Size &amp; Weight</b> Cassettes: A5R-A3, 64-256 gsm Bypass: A6R-320 x 460 mm, 64-280 gsm, banner paper (305 x 1,200 mm, 90-163 gsm)<sup>1)</sup></p> <p><b>Paper Capacity</b> 2 x 550 sheets (Cassettes), 100 sheets (Bypass) Maximum: 3,700 sheets</p> <p><b>Automatic Duplex Controller Type</b> A5R-A3+, 64-256 gsm</p> <p><b>Memory Interface</b> Toshiba e-BRIDGE 80 GB HDD, 1.5 GB RAM</p> <p><b>Dimensions &amp; Weight</b> 10/100/1000 BaseT (incl. IPv6), High-Speed USB 2.0, WLAN<sup>2)</sup> (IEEE802.11b/g), Bluetooth<sup>2)</sup> 699 x 808 x 759 mm (W x D x H), ~ 121 kg</p>
<p><b>Print</b></p>	<p><b>Resolution</b> Max. 600 x 600 dpi, 8 bit per colour channel</p> <p><b>Page Description Languages Supported Systems</b> XPS, PCL6 and PostScript 3 compatible Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novel Netware (NDPS), Citrix, SAP, AS/400</p> <p><b>Colour Modes</b> Auto-Colour (ACS), Colour, Twin Colour, B&amp;W</p> <p><b>Colour Settings</b> Brightness, Saturation, Contrast, Colour Balance, ICC profiles management</p> <p><b>Print Functions</b> Universal Driver, Driver templates, Driver plug-ins, Hold print, Print from USB, Tandem Printing</p>
<p><b>Scan</b></p>	<p><b>Resolution</b> Max. 600 x 600 dpi, 8 bit per colour channel</p> <p><b>Scan Speed</b> Colour &amp; B&amp;W: Up to 57 ppm (300 dpi)</p> <p><b>Scan Modes</b> Auto-Colour (ACS), Colour, Greyscale, B&amp;W</p> <p><b>File Formats</b> JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF, Searchable PDF<sup>2)</sup> (and other editable formats like DOC, XLS, RTF, TXT, PDF/A)<sup>2)</sup></p> <p><b>Scan Functions</b> WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Meta Scan<sup>2)</sup>, Scan to Box (e-Filing), TWAIN 1.7/1.8/1.9</p>
<p><b>Copy</b></p>	<p><b>Resolution</b> Scan: 600 x 600 dpi, 10 bit per colour channel Print: 600 x 600 dpi, 8 bit per colour channel</p> <p><b>First Copy Output time</b> 2,400 x 600 dpi, B&amp;W with smoothing Colour: Approx. 8.4/8.4/8.4/8.4/6.8 seconds B&amp;W: Approx. 6.5/6.5/6.5/6.5/5.2 seconds</p> <p><b>Zoom</b> 25-400% (platen), 25-200% (RADF)<sup>2)</sup></p> <p><b>Copy Modes</b> Text, Text/Photo, Photo, Printed Image, Map</p> <p><b>Colour Modes</b> Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&amp;W</p> <p><b>Colour Settings</b> Hue, Saturation, Colour Balance, 5 One-touch Modes, RGB Adjustment</p>
<p><b>Fax<sup>2)</sup></b></p>	<p><b>Communication</b> Super G3, G3 - (opt. 2<sup>nd</sup> line), Internet Fax T.37</p> <p><b>Transmission Speed</b> Approx. 3 seconds per page</p> <p><b>Compression</b> JBIG, MMR, MR, MH</p> <p><b>Network-Fax</b> Driver for Windows 7/Vista/XP (32/64 bit)</p> <p><b>Incoming Fax Routing</b> To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing</p>
<p><b>System &amp; Security</b></p>	<p><b>Device Management</b> e-BRIDGE Fleet Management System<sup>2)</sup>, TopAccess for remote administration and configuration</p> <p><b>System Features</b> e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan/Fax preview, RIP-while-Print, e-BRIDGE Open Platform<sup>2)</sup>, Job Skip</p> <p><b>Accounting &amp; Security</b> Role Based Access, LDAP support, 1,000 department codes &amp; 10,000 user codes, card reader<sup>2)</sup>, private print, standard data encryption, Data Overwrite Enabler<sup>2)</sup>, IP and MAC address filter, port filter, support of SSL and IPsec<sup>2)</sup> protocols, IEEE802.1x support, IEEE2600.1 compliant, Scan to secure PDF</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 gsm if not otherwise mentioned.</p>

<p><b>OPTIONS</b></p>
<p><b>RADF – MR-3021 / MR-3022</b> 100-sheet capacity, A5R-A3, 35-157 gsm</p>
<p><b>HANGING FINISHER – MJ-1031</b> 1 tray, 1,000-sheet capacity 50-sheet single position stapling A5R-A3, 64-105 gsm (stapling mode) 411 x 595 x 383 mm (W x D x H), ~ 12 kg</p>
<p><b>MULTI-STAPLING FINISHER – MJ-1101</b> 2 trays, 2,250-sheet capacity 50-sheet multi-position stapling A5R-A3, 64-105 gsm (stapling mode) 535 x 598 x 1,092 mm (W x D x H), ~ 34 kg</p>
<p><b>SADDLE-STITCH FINISHER – MJ-1106</b> 2 trays, 3,250-sheet capacity 50-sheet multi-position stapling 5-sheet center-folding Saddle-stitched booklets of up to 60 pages A5R-A3, 64-105 gsm (stapling mode) 617 x 603 x 1,085 mm (W x D x H), ~ 70 kg</p>
<p><b>HOLE PUNCH UNIT – MJ-6103</b> Option for Finisher MJ-1101/MJ-1106 Available in 2 holes (E), 4 holes (F), 4 holes (S) 112 x 573 x 323 mm (W x D x H), ~ 7 kg</p>
<p><b>PAPER FEED PEDESTAL – KD-1027</b> 550 sheets (1 cassette), A5R-A3, 64-256 gsm 623 x 643 x 320 mm (W x D x H), ~ 21 kg</p>
<p><b>LARGE CAPACITY FEEDER – KD-1028A4</b> 2,500-sheet capacity, A4, 64-105 gsm 623 x 643 x 308 mm (W x D x H), ~ 27 kg</p>
<p><b>OTHER OPTIONS</b> DESK – MH-1710 CASSETTE – MY-1035 FAX BOARD – GD-1250EU DATA OVERWRITE ENABLER – GP-1070 e-BRIDGE ID-GATE – TWN3XX WIRELESS LAN MODULE – GN-1060 BLUETOOTH MODULE – GN-2010 META SCAN ENABLER – GS-1010 WEB-SERVICES ENABLER – GS-1020 IPsec ENABLER – GP-1080 e-BRIDGE Re-Rite – GB-1280</p>
<p><sup>1)</sup> With Toshiba waterproof banner paper up to 230 gsm <sup>2)</sup> Optional</p>

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2011 Toshiba TEC. DS-4540cBNE1104

**TOSHIBA TEC UK  
IMAGING SYSTEMS LTD**

ABBEY CLOISTERS, ABBEY GREEN,  
CHERTSEY, SURREY KT16 8RB  
TEL 01932 580100 FAX 01932 580101  
WWW.TOSHIBA.CO.UK/IMAGING

Jav.61244.0511a



**TOSHIBA**  
Leading Innovation >>>

6BY0COP1567