



e-STUDIO5520c PRO

e-STUDIO6520c PRO

e-STUDIO6530c PRO



<p>General</p>	<p>Print & Copy Speed Colour: 55/65/65 ppm (A4), 27/30/30 ppm (A3) B&W: 55/65/75 ppm (A4), 27/30/37 ppm (A3) Approx. 70 seconds from low-power mode</p> <p>Warm-up Time</p> <p>Paper Size & Weight Cassettes: A5R-SRA3, 64-256 gsm Tandem LCF²⁾: A4, 64-256 gsm Bypass: A6R-SRA3, 64-300 gsm, banner paper³⁾ 313 x 1,200 mm, 64-256 gsm</p> <p>Paper Capacity 4 x 540 sheets (Cassettes) or 2 x 540 sheets (Cassettes) + 2,320 sheets (Tandem LCF)²⁾, 100 sheets (Bypass)</p> <p>Automatic Duplex Maximum: 6,000²⁾ sheets with external LCF¹⁾ Up to SRA3 and 256 gsm</p> <p>Controller Type EFI Fiery System 8e, Toshiba e-BRIDGE</p> <p>Memory EFI: 80 GB HDD, 512 MB (max. 1,024 MB) RAM e-BRIDGE: 80 GB HDD, 2.0 GB RAM</p> <p>Interface 10/100/1000BaseT USB 2.0 host port</p> <p>Dimensions & Weight 980 x 853 x 1,540 mm (W x D x H), ~ 252 kg</p>
<p>Print</p>	<p>Resolution Max. 600 x 600 dpi, 8 bit per channel Max. 1,200 x 1,200 dpi, 2 bit per channel</p> <p>Page Description Language Adobe PostScript 3, Native support for PDF1.4-1.6, PDF/X, TIFFv6, PS and EPS</p> <p>Supported Systems Windows 2000, Windows XP/Server2003/ Vista (32/64 bit), Mac OS X (PPC & Intel)</p> <p>Colour Modes Auto-Colour (ACS), Colour, B&W</p> <p>Colour Settings ICC based in-RIP colour management: CMYK, RGB, CIE Lab and spot colour¹⁾ support, device link profile support</p>
<p>Scan</p>	<p>Resolution Max. 600 x 600 dpi, 8 bit per channel</p> <p>Scan Speed Colour & B&W: Up to 77 pages/min. (300 dpi)</p> <p>Document Feeder¹⁾ Max. 100 sheets, A5R-A3, 35-209 gsm</p> <p>Scan Modes Auto-Colour (ACS), Colour, Greyscale, B&W</p> <p>File Formats JPEG, Multi/Single Page TIFF, Multi/Single Page XPS, Multi/Single Page PDF, Secure PDF, Slim PDF (high compression),</p> <p>Scan Functions Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, local), Scan to e-Filing/Mailbox, Scan to Hold Queue</p>
<p>Copy</p>	<p>Resolution Scanning: 600 x 600 dpi, 10 bit per channel Printing: 600 x 600 dpi, 8 bit per channel 2,400 x 600 dpi, B&W with smoothing</p> <p>First Copy Colour: Approx. 6.5 seconds B&W: Approx. 5.3/5.3/4.6 seconds</p> <p>Zoom 25-400% (platen glass), 25-200% (RADF)¹⁾</p> <p>Copy Modes Text, Text/Photo, Photo, Printed Image, Map</p> <p>Colour Modes Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&W</p> <p>Colour Settings Hue, Saturation, Colour Balance, 5 One-touch Modes, RGB Adjustment</p>
<p>Fax¹⁾</p>	<p>Communication Super G3, G3 - (opt. 2nd line), Internet Fax T.37</p> <p>Transmission Speed Approx. 3 seconds per page</p> <p>Compression JBIG, MMR, MR, MH</p>
<p>System & Security</p>	<p>Device Management This is a Command workstation for monitoring and managing of print jobs, TopAccess remote administration & configuration e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan preview, Print from USB, RIP-while-print, black overprinting, composite overprinting</p> <p>System Features Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, secure print, standard data encryption, Data Overwrite Enabler¹⁾, IP address filter, port filter, support of SSL and IPsec¹⁾ protocol, Scan to secure PDF</p> <p>Accounting & Security</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 gsm if not otherwise mentioned.</p>

OPTIONS

MULTI-STAPLE FINISHER – MJ-1103

2 trays, 3,250 sheet capacity
50 sheet multi-position staple
A5R-A3, 64-105 gsm (staple mode)
617 x 603 x 1,085 mm (W x D x H), ~ 40 kg

SADDLE-STITCH FINISHER – MJ-1104

2 trays, 3,250 sheet capacity
50 sheet multi-position stapling
Saddle-stitched booklets of up to 60 pages
A5R-A3, 64-105 gsm (staple mode)
617 x 603 x 1,085 mm (W x D x H), ~ 70 kg

HOLE PUNCH UNIT – MJ-6102

Option for Finisher MJ-1103/MJ-1104
Available in 2-holes (E), 4-holes (F),
112 x 573 x 323 mm (W x D x H), ~ 7 kg

LARGE CAPACITY FEEDER – MP-2501A

2,500 sheet capacity, A4, 64-256 gsm
360 x 552 x 542 mm (W x D x H), ~ 29 kg

GRAPHIC ARTS KITS

EFI Spot-On, EFI Hot Folders, EFI Auto Trapping

EFI COLOUR PROFILER

Profiling Software incl. ES-1000 Spectrophotometer

OTHER OPTIONS

2ND LINE FAX GD-R60
FAX BOARD GD-1270EU
DATA OVERWRITE KIT GP-1070
IMAGING ACCELERATION BOARD GE-1170
META SCAN ENABLER GS-1010
WEB-SERVICES ENABLER GS-1020

¹⁾ Optional
²⁾ e-STUDIO5520c PRO tandem LCF version only
³⁾ Optional memory extension required

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2009 TOSHIBA TEC. DS6530cPROGB0901

TOSHIBA TEC UK IMAGING SYSTEMS LTD

ABBAY CLOISTERS, ABBAY GREEN,
CHERTSEY, SURREY, KT16 8RB.
TEL 01932 580100 FAX 01932 580101
WWW.TOSHIBA.CO.UK/IMAGING