

**TASKalfa** 

> PRINT > COPY > SCAN > FAX

**TASKalfa 6551ci**

A3 COLOUR MULTIFUNCTIONAL

# THE DEVICE FOR PERFECT COLOUR



- > Up to 65 A4 pages per minute in black and white and colour
- > Intuitive and customisable touch screen control panel
- > 4 GB RAM + 320 GB HDD
- > Standard network and printing as well as colour scanning
- > Excellent image quality thanks to advanced colour technology – Fiercy compatible
- > Individual paper handling options including booklet and tri-folding
- > Long-life components provide unprecedented efficiency and reliability

The TASKalfa 6551ci incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 6551ci provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.



The TASKalfa 6551ci incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 6551ci provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

## GENERAL

### Technology

KYOCERA Laser Colour, HyPAS™ solution platform

### Engine speed (pages per minute)

Up to 65/32 A4/A3 in colour and in black and white

### Resolution

600 x 600 dpi, Multi-bit technology for print quality of 9,600 dpi equivalent x 600 dpi

### Warm-up time from power on

Approx. 60 seconds or less

### Time to first page

Approx. 5.4 sec. or less in black and white; 6.2 sec. or less in colour

### CPU

Freescale QorIQ P1022 Dual Core 1067 MHz

### Memory

4 GB RAM + 320 GB minimum HDD

### Standard interfaces

USB 2.0 (Hi-Speed) x 4, USB Host 2.0, Fast Ethernet 10BaseT/100BaseTX/1000BaseT, slot for optional print server, slot for optional SD, SDHC card, slot for optional fax system

### Dimensions (W x D x H) – main unit

685 x 801 x 1,053 mm (DP, operation panel not included)  
1,039 x 801 x 1,347 mm (DP, operation panel included)

### Weight: Main unit approx. 190 kg

Power source: AC 220 V ~ 240 V, 50/60 Hz

### Power consumption

Printing: 1,480 W (in colour), 1,350 W (in black and white)

Ready mode: 300 W

Sleep mode: 1.8 W

### Noise (sound pressure level ISO 7779/ISO 9296)

Printing: black and white 53.9 dB(A) LpA / colour 54.0 dB(A) LpA

Stand-by: 37.9 dB(A) LpA

### Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.  
RoHS compatibility

## PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

### Input capacity

150-sheet multi-purpose tray, 60–300 g/m<sup>2</sup> (banner 136-165 g/m<sup>2</sup>), A6R–305 x 457 mm, banner max. 305 x 1,220 mm;  
2 x 1,500-sheet high-capacity paper deck, 60–256 g/m<sup>2</sup>, A4, B5;  
2 x 500-sheet universal paper cassette, 60–256 g/m<sup>2</sup>, A5R–305 x 457 mm

Max. input capacity with options: 7,650 sheets A4

**Document processor:** (single pass duplex scanning) 270 sheets;

35–220 g/m<sup>2</sup> (simplex), 50–220 g/m<sup>2</sup> (duplex); A5R–A3

**Duplex unit:** Duplex as standard supports A5R–305 x 457 mm, 60–256 g/m<sup>2</sup>

**Output capacity:** Standard job separator tray 70 sheets, optional copy tray (D): upper 100 sheets, lower 250 sheets.  
Max. optional output capacity 4,300 sheets

## PRINT FUNCTIONS

**Controller language:** PRESCRIBE IIc

**Emulations:** PCL6 (PCL5c/PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print

**Operating systems:** All current Windows operating systems, Mac OS X Version 10.4 or higher, UNIX LINUX, as well as other operating systems on request.

**Fonts/barcodes:** 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

**Print features:** Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, Private Print, job storage and job management functionality

## COPY FUNCTIONS

**Max. original size:** A3

**Continuous copying:** 1–9,999

**Zoom range:** 25–400% in 1% steps

**Preset magnification ratios:** 5 reductions/5 enlargements

**Digital features:** Scan-once-copy-many, electronic sort, 2in1 and 4in1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay plus poster mode, margin shift

**Exposure mode:** Auto, manual: 7 or 13 steps

**Image adjustments:** Text + photo, text, photo, map

## SCAN FUNCTIONS

**Functionality:** Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan

**Scan speed (A4, 300 dpi, Dual Scan) black and white 200 images per minute, colour 200 images per minute**

**Scan resolution:** 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi, (256 greyscales)

**Max. scan size:** A3

**Original recognition:** Text, photo, text + photo, optimised for OCR

**Network protocol:** TCP/IP

**File types:** PDF (high compression, encrypted, PDF/A), Searchable PDF, JPEG, TIFF, XPS

## FAX FUNCTIONS (OPTIONAL)

**Compatibility:** ITU-T Super G3

**Modem speed:** Max. 33.6 kbps

**Transmission speed:** Max. 3 seconds (JBIG)

### Fax resolution

Normal: 200 x 100 dpi

Fine: 200 x 200 dpi

Superfine: 200 x 400 dpi

Ultrafine: 400 x 400 dpi

**Max. original size:** A3

**Compression method:** JBIG, MMR, MR, MH

**Memory:** Standard 12 MB, max. 128 MB

**Features:** Opt. Internet-fax, network faxing, rotate transmission, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system

## CONSUMABLES

Average continuous toner yield in accordance with 5% coverage A4.

**TK-8705K Toner-Kit:** Toner Black for 70,000 pages

**TK-8705C, TK-8705M, TK-8705Y Toner-Kits:**

Toner cyan, magenta, yellow for 30,000 pages

**WT-861 Waste Toner Bottle:** 150,000 sheets (in accordance with 5% coverage. Colour: black and white = 6:4)

**Staple cartridge:** SH-10 for BF-730, SH-12 for DF-790

## OPTIONS

### Fax System (W)B

### Internet Fax Kit (A)

**Printing System (14):** Fiery Controller

**Printing System Interface Kit (B):** Interface board for Fiery

### Paper handling

#### PF-730(B) Paper feeder

2 x 500 sheets, 60–256 g/m<sup>2</sup>, 305 x 457 mm, folio

#### PF-740(B) Paper feeder

3,000 sheets, 60–256 g/m<sup>2</sup>, A4, B5, letter

**PF-770 A4 side deck:** 3,000 sheets, 60–300 g/m<sup>2</sup>, A4, B5

#### PF-780(B) Multimedia tray and paper path unit

500 sheets, 60–256 g/m<sup>2</sup>, A5R–305 x 457 mm

#### DF-790(C) Document finisher

Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-730 attachment); max. 60–300 g/m<sup>2</sup>; max. B5R–305 x 457 mm

Sub-tray: 200 sheets A4; 60–300 g/m<sup>2</sup>; A6R–305 x 457 mm

Sub-tray (top): 100 sheets; 60–300 g/m<sup>2</sup>; A6R–A4

Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5–305 x 457 mm

#### PH-7C/PH-7D Punch unit for DF-790(C)

2-hole/4-hole/Swedish type, 60–300 g/m<sup>2</sup>, A5R–A3

#### MT-730(B) Mailbox sorter for DF-790(C)

7 bins x 100 sheets A4, 50 sheets A3/B4, 60–163 g/m<sup>2</sup>

#### BF-730 Booklet and tri-folding unit for DF-790(C)

Half folding: 60–256 g/m<sup>2</sup>, A3, B4, A4R

Booklet: max. 16 sheets (64 pages, 60–90 g/m<sup>2</sup>)

Non-staple folding: max. 5 sheets (60–90 g/m<sup>2</sup>)

Tri-folding: 60–105 g/m<sup>2</sup>, A4R

Multi tri-folding: 5 sheets (60–90 g/m<sup>2</sup>), 3 sheets (91–105 g/m<sup>2</sup>)

### Banner Guide (A)

Banner paper feeding guide, up to 10 sheets

### Fax memory

**MM-16-128:** Image memory (128 MB)

### Security

#### Data security kit (E)

In line with ISO 15408 (Common Criteria) with security level EAL3

#### Printed Document Guard Kit (B)

**USB IC Card Reader:** Card Authentication Kit (B),

Card Reader Holder (E)

#### UG-33 AC: ThinPrint support

**UG-34 AC:** Emulation (IBM Proprinter/EPSON LQ-850)

### Optional interface

**IB-50:** Gigabit-Ethernet board 10BaseT/100BaseTX/1000BaseT

**IB-51:** Wireless Lan Interface

**Copy tray (D):** upper tray 100 sheets, lower tray 250 sheets



HyPAS™

KYOCERA Document Solutions (UK) Ltd  
Eldon Court, 75-77 London Road, Reading RG1 5BS  
Tel: 0118 931 1500 – Fax: 0118 931 1108  
www.kyoceradocumentsolutions.co.uk – info@duk.kyocera.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

YOUR KYOCERA BUSINESS PARTNER

 **KYOCERA**  
Document Solutions